Check List
RITTER MultiGas Sensors

Please use a separate check list for each gas stream
* required data

Customer:

Application: Biogas ☐ Process control ☐ Automotive ☐
Ambient ☐ Stack gas/CEM ☐
Other:

* Gases to be analysed[1]:							
CH_4 ☐	Range[2]: 0 ~ Select	CO_2 ☐	Range[2]: 0 ~ Select
CO ☐	Range[2]: 0 ~ Select	N_2O ☐	Range[2]: 0 ~ Select
C_nH_m[3] ☐	Range[2]: 0 ~ Select	CF_4 ☐	Range[2]: 0 ~ Select
SF_6 ☐	Range[2]: 0 ~ Select	O_3 ☐	Range[2]: 0 ~ Select
Cl_2 ☐	Range[2]: 0 ~ Select	H_2S ☐	Range[2]: 0 ~ Select
SO_2 ☐	Range[2]: 0 ~ Select	NO ☐	Range[2]: 0 ~ Select
NO_2 ☐	Range[2]: 0 ~ Select	O_2 ☐	Range[2]: 0 ~ Select
H_2O[4] ☐	Range[2]: 0 ~ Select		
Other:		Range: 0 ~	
Other:		Range: 0 ~	

[1] Selected gases and ranges might not always be combinable. Will be reviewed by RITTER.
[2] Measurement range = calibration range; cannot be changed by user after calibration. Custom ranges on request. Please state in field “Other” and/or “Miscellaneous”.
[3] Calibration with Propane
[4] H_2O vapour > 2 vol.% with heated and thermostatted casing only to avoid condensation

* Remaining gas component(s) incl. concentration(s) in gas to be measured. **Must add up to approx. 100 vol.%** together with the above “Gases to be analysed”.

Environmental Conditions:
* Temperature min/max: / °C
* Humidity min/max: / %rH
* Pressure min/max: / mbar
* Gas Flow min/max: / ltr/h

Data Interface: USB ☐ RS232 ☐ CANopen[5] ☐ CANbus[5] ☐
Options: Pressure sensor[5] ☐ Humidity sensor[5] (0-95%RH) ☐
[5] (Surcharge) Analog Output[5]: 0-2V ☐ 0-5V ☐ 0-10V ☐
Heated and thermostatted casing[5] ☐

Miscellaneous:

Name: **Company**: **Country:**

Date:

Send to our distribution partner
in your region ⇒ .....https://www.ritter.de/en/worldwide
or to RITTER Germany ⇒.....mailbox@ritter.de

Rev. 22-05-12