


RITTER Bellows-type Gas Meter BG 16

RITTER DATA SHEET / BELLOWS-TYPE GAS METERS









Legend

- 1. Gas inlet
- 2. Handle
- 3. Gas outlet
- 4. Pulse generator port (option)
- **5.** Removable cover

Performance Data

Minimum flow Q _{min}	160	ltr/h	Maximum gas inlet pressure	50	mbar
Standard flow Q _{standard}	15,000	ltr/h	Minimum differential pressure ⁽¹⁾	1	mbar
Maximum flow Q _{max}	25,000	ltr/h	Minimum dial division	0.4	ltr
Measurement accuracy ⁽²⁾	2	%	Indication dial plate	100	ltr
Measuring cavity capacity	10	ltr/U	Maximum indication value ⁽³⁾	999,999,990	ltr
Temperature range	-20 to +50	°C	Weight	11	kg

- > (1) Differential pressure (= pressure loss) gas inlet gas outlet
- > (2) Across the measuring range in relation to the calibration value at nominal flow
- > (3) Standard Totalizing Roller Counter

No reverse flow direction possible!

Models (materials)

- > Casing: zinc-coated steel sheet (soldered) with outside also lacquered
- > Measuring unit: Tinplate
- > Bellows (within measuring unit): textile-reinforced nitrile rubber (Perbunan®)
- > Rod linkage: Polyamide
- > Slide gate: Bakelite

Standard Equipment

- > 8 or 9-digit Totalizing Roller Counter
- > Large, One-needle Dial
- Magnetic Coupling (between the measuring drum and counting mechanism)
- > Screw Connection 2" (G 2 A, DIN ISO 228)
- > Twin-Chamber Measuring Unit

Built-in Options

- LCD Display , resettable, 8-digit (replaces Totalizing Roller Counter)
- > Pulse Generator , standard or Ex-proof version (for connecting Electronic Display Unit/Computer)

V 2.1 / Rev. 2023-05-24 / Subject to alterations.

The most recent version of this data-sheet can be found at ... https://www.ritter.de/en/bg-16/

Dr.-Ing. RITTER Apparatebau GmbH & Co. KG · Coloniastrasse 19-23 · D-44892 Bochum · Germany For questions please contact mailbox@ritter.de or your local distribution partner (on our overview page)

Accessories

- > Thermometer (BG)
- > Manometer for pressure pmax = 60 mbar
- > Electronic Display Unit »EDU 32 FP«, displays volume and calculates flow rate via RS232 and analog-output in realtime (pulse generator required)
- > Nozzles for flexible tube connection