


RITTER Bellows-type Gas Meter BG 6

RITTER DATA SHEET / BELLOWS-TYPE GAS METERS









Legend

- 1. Gas inlet
- 2. Gas outlet
- **3.** Pulse generator port (option)
- 4. Removable cover

Performance Data

| Minimum flow Q _{min} | 60 | ltr/h | Maximum gas inlet pressure | 300 | mbar |
|-------------------------------------|------------|-------|---|------------|------|
| Standard flow Q _{standard} | 5,000 | ltr/h | Minimum differential pressure (1) | 1 | mbar |
| Maximum flow Q _{max} | 10,000 | ltr/h | Minimum dial division | 0.2 | ltr |
| Measurement accuracy ⁽²⁾ | 2 | % | Indication dial plate | 20 | ltr |
| Measuring cavity capacity | 3.5 | ltr/U | Maximum indication value ⁽³⁾ | 99,999,999 | ltr |
| Temperature range | -20 to +50 | °C | Weight | 6.4 | kg |
| | | | | | |

- > (1) Differential pressure (= pressure loss) gas inlet gas outlet
- > (2) Across the measuring range in relation to the calibration value at nominal flow
- > ⁽³⁾ Standard Totalizing Roller Counter

No reverse flow direction possible!

Models (materials)

- > Casing: zinc-coated steel sheet (soldered) with outside also lacquered
- > Measuring unit: Tinplate
- > Bellows (within measuring unit): textile-reinforced nitrile rubber (Perbunan®)
- > Rod linkage: Polyamide
- > Slide gate: Bakelite

Standard Equipment

- > 8 or 9-digit Totalizing Roller Counter
- > Large, One-needle Dial
- Magnetic Coupling (between the measuring drum and counting mechanism)
- > Thread connection 1-1 / 4 "(G 1-1 / 4 A, DIN ISO 228)
- > Twin-Chamber Measuring Unit

Built-in Options

- LCD Display , resettable, 8-digit (replaces Totalizing Roller Counter)
- > Pulse Generator, standard or Ex-proof version (for connecting Electronic Display Unit/Computer)

V 3.0 / Rev. 2023-05-24 / Subject to alterations.

The most recent version of this data-sheet can be found at ... https://www.ritter.de/en/bg-6/

Dr.-Ing. RITTER Apparatebau GmbH & Co. KG · Coloniastrasse 19-23 · D-44892 Bochum · Germany For questions please contact mailbox@ritter.de or your local distribution partner (on our overview page)

Accessories

- > Thermometer (BG)
- > Manometer for pressure pmax = 60 mbar
- > Electronic Display Unit »EDU 32 FP«, displays volume and calculates flow rate via RS232 and analog-output in realtime (pulse generator required)
- > Nozzles for flexible tube connection